

COMPRESSORI D'ARIA CON TRASMISSIONE A CINGHIA

BELT DRIVEN AIR COMPRESSORS
COMPRESSEURS AVEC D'AIR TRANSMISSION À COURROIE
LUFTKOMPRESSOREN MIT RIEMENANTRIEB



AIR COMPRESSORS



GS17/150/330/CAR/T



1 Collettore di raffreddamento.



2 Doppia uscita.



3 Ruota pivotante.

150 ÷ 200

MODELLO <i>Model</i>	CODICE <i>Code</i>													€			
		Litri <i>Liters</i>	Litri/min <i>Liters/min</i>	CFM	min-1	Cilindri <i>Cylinders</i>	Stadi <i>Stages</i>	bar	psi	kW	HP	Volt	Hz		dB/A	L x P x H <i>cm</i>	Kg
GS10/150/286/CAR/M	AF 012	150	286	10,1	1.300	2	1	10	145	2,2	3	230	50	72	135x45x100	80	1.202,00
GS10/150/306/CAR/T	AF 013	150	306	10,8	1.400	2	1	10	145	2,2	3	400	50	72	135x45x100	80	1.219,00
GS17/150/320/CAR/M	AF 014	150	320	11,3	1.500	2	1	10	145	2,2	3	230	50	74	135x45x98	78	1.076,00
GS17/150/330/CAR/T	AF 015	150	330	11,6	1.550	2	1	10	145	2,2	3	400	50	74	135x45x98	78	1.103,00
GS10/200/286/CAR/M	AF 017	200	286	10,1	1.300	2	1	10	145	2,2	3	230	50	72	150x50x105	90	1.236,00
GS10/200/306/CAR/T	AF 018	200	306	10,8	1.400	2	1	10	145	2,2	3	400	50	72	150x50x105	90	1.263,00
GS17/200/320/CAR/M	AF 019	200	320	11,3	1.500	2	1	10	145	2,2	3	230	50	74	150x50x103	88	1.109,00
GS17/200/330/CAR/T	AF 020	200	330	11,6	1.550	2	1	10	145	2,2	3	400	50	74	150x50x103	88	1.136,00