



HL-42F | CE

4POST 4TON WHEEL ALIGNMENT LIFT



FEATURE

- Hydraulic cylinder located in the fixed platform and is thus perfectly protected.
- High-resistance galvanized and pre-stretched lifting cable.
- Adjustable parking ratchet rails ensure the platforms and cross members horizontal within 4 wheel alignment tolerances.
- Automatic spring loaded eccentric brake system in the event of cable breakage and ensures complete stability during parking.
- Self lubricated large diameter pulleys and maintenance-free bushes.
- Auxiliary lift table built in the platforms for wheel free operation.
- Auto-pneumatic rear slip plates locking device.
- Front turn-table recesses and rear sliding plates for 4-wheel alignment operation.
- Two step descending system gives full foot protection. (CE)
- Hydraulic hand-pump for emergency ascend/descend. (CE)
- De-synchronization detecting electronic photo-cell. (CE)
- Descend alarm signal. (CE) • Lighting kits 4pcs. (OPTION)

SPECIFICATION

Model No.	HL-42F
Lifting Capacity (kg)	Body : 4,000 / Jack : 3,000 kg
Max.Lifting Height (mm)	Body : 1,810 / Jack : 390 mm
Dimension (mm)	5,775(L) X 3,542(W) X 2,210(H)
Power Supply & Motor	3ph : 3HP, 4P, 220/380V, 50/60 Hz
Net Weight	1,950 kg

LAY-OUT

