



Air Ratchets



3/8 inch RATCHET

The CL1501 delivers 55 ft.-lbs. of torque to install fasteners in tight compartments. Ideal for automotive engine repair work.

- Rubber grip for added comfort
- Heat treated ratcheting components for increased durability

CL1501

Drive	3/8 in.
Working Torque	10-45 ft.-lbs.
Max Torque	55 ft.-lbs.
Free Speed RPM	155
Air Consumption Avg.	4.8 SCFM
Air Consumption Cont.	19.2 SCFM
Air Inlet	1/4 in. NPT
Min. Hose Size	3/8 in.
Weight	2.5 lbs.



1/2 inch RATCHET

Need extra torque? The CL1548 delivers 90 ft.-lbs. of torque to handle large fasteners on engines and heavy machinery.

- The extra long handle provides additional leverage
- Heavy duty head design for durability and longer life

CL1548

Drive	1/2 in.
Working Torque	10-75 ft.-lbs.
Max Torque	90 ft.-lbs.
Free Speed RPM	150
Air Consumption Avg.	8 SCFM
Air Consumption Cont.	32 SCFM
Air Inlet	1/4 in. NPT
Min. Hose Size	3/8 in.
Weight	4.3 lbs.

Rivet Tools



RIVET GUN

The CL1539 is ideal for automotive and construction assembly work. The hardened steel jaws set rivets in steel up to 3/16-in thick.

- 2,000 lbs of pull for tough jobs
- Four nose pieces included: 3/32, 1/8, 5/32, and 3/16 inch.
- Effortless trigger action eases the repetitive action of popping rivets

CL1539

Rivet Sizes	3/32, 1/8, 5/32, 3/16 in.
Pulling Power	2000 lbs.
Air Consumption Avg.	0.2 SCFM
Air Consumption Cont.	1.1 SCFM
Air Inlet	1/4 in. NPT
Min. Hose Size	3/8 in.
Weight	3.5 lbs.

Needle Scalers



NEEDLE SCALER

The CL1581 needle scaler delivers 4,800 blows per minute for fast removal of rust, paint, weld slag, or dirt.

- Durable, hardened steel construction
- Compact, in-line design
- Stroke length 1.3 in.

CL1581

Needle Quantity	12
Needle Size	1/8-in.
Blows/Min.	4800
Air Consumption Avg.	3.1 SCFM
Air Consumption Cont.	6.9 SCFM
Air Inlet	1/4-in. NPT
Min. Hose Size	3/8-in.
Weight	2.9 lbs.



PISTOL GRIP NEEDLE SCALER

The CL1582 features a pistol grip design and is ideal for work on curved, uneven surfaces.

- Delivers 4,800 blows per minute
- Constructed with 19 heat treated needles
- Stroke length 1.8 in.

CL1582

Needle Quantity	19
Needle Size	1/8-in.
Blows/Min.	4800
Air Consumption Avg.	8.3 SCFM
Air Consumption Cont.	18.4 SCFM
Air Inlet	1/4 in. NPT
Min. Hose Size	3/8-in.
Weight	4.3 lbs.