



Trasmissione a cinghia Poly-V.



Sistema di separazione.



GSE10/300



GSR15/500

GSE5/300 > GSR15/500

 MODELLO Model	 Litri Liters	 Litri/min Liters/min	 CFM	 bar	 psi	 HP	 kW	 dB/A	 Volt	 Kg	 L x P x H cm	
Avviamento diretto - Direct starting - Démarrage direct - Direkte Anschaltung												
GSE5/300	300	620	21,90	8	116	5,5	4	66	400/50/3	210	165x60x139	6.436,00
		500	17,65	10	145							6.436,00
Avviamento diretto - Direct starting - Démarrage direct - Direkte Anschaltung												
GSE7/300	300	890	31,4	8	116	7,5	5,5	66	400/50/3	220	165x60x139	6.587,00
		700	24,71	10	145							6.587,00
		590	20,83	13	188							6.858,00
Avviamento stella/triangolo - Star/delta starting - Démarrage étoile/triangle - Anschaltung über Stern/Dreieck												
GSE10/300	300	1250	44,12	8	116	10	7,5	66	400/690/3	227	165x60x139	7.490,00
		1000	35,3	10	145							7.490,00
		850	30	13	188							7.760,00
Avviamento stella/triangolo - Star/delta starting - Démarrage étoile/triangle - Anschaltung über Stern/Dreieck												
GSE10/500	500	1250	44,12	8	116	10	7,5	66	400/690/3	287	190x60x151	7.744,00
		1000	35,3	10	145							7.744,00
		850	30	13	188							8.068,00
Avviamento stella/triangolo - Star/delta starting - Démarrage étoile/triangle - Anschaltung über Stern/Dreieck												
GSR15/500	500	1800	63,54	8	116	15	11	68	400/690/3	310	190x70x200	8.793,00
		1500	52,95	10	145							8.793,00
		1300	45,89	13	188							9.118,00