

WIRELESS REFRIGERANT CHARGING SCALE



98315 with solenoid



When remote is out of range the unit will automatically pause. This pause mechanism allows unit to restart when remote is back in range.

CALIBRATION CERTIFICATE AVAILABLE UPON REQUEST

FEATURES:

- Wireless unit prevents unwanted tangles in wires
- Easily store the remote in the body of the platform
- Keypad provides synchronization and zeroing
- Extremely accurate weight sensor
- Magnet on remote allows easy placement on fixtures
- Battery life symbol for platform and remote constantly displayed on LCD
- Wireless signal strength indicator conveniently displays on remote

FUNCTIONS:

• CHARGE PROGRAMMING:

Allows user to program desired quantities. Before charge is complete, an alarm will sound allowing ample time to turn off refrigerant supply.

• PAUSE/CHARGE (98315 model only):

This feature allows user to stop and continue charging.

• TANK CAPACITY PROGRAMMING:

Empty/full tank feature allows user to know the amount of refrigerant in the tank at any time.

• REPEAT (98315 model only):

Allows user to charge previously stored amount.

SPECIFICATIONS:

- Capacity: 243 lbs (110 kg)
- Accuracy: $\leq \pm 0.05\%$ of reading
- Resolution: 0.05 lb / 0.5 oz / 0.01 kg
- 3 hrs auto off function
- Operating temperature: 32°F to 120°F (0°C to 49°C)
- Battery life: approximately 20 hours
- 31 cm platform
- Accepts all US & EU standard cylinders



REMOTE RANGE:
100 FEET (30 M),
LINE OF SIGHT

98310 Wireless Refrigerant Charging Scale

98315 Wireless Refrigerant Charging Scale with Solenoid

ELECTRONIC TANK HEATER BLANKET



The Mastercool refrigerant tank heater blanket speeds up recharging time.

- Assures total discharge of refrigerant from 30 lb and 50 lb tanks. Heats tanks to 125°F resulting in maximum pressure of 185 psi for R134a
- Quick working 300W heater element
- An excellent complement to all Mastercool refrigerant scales

98250 110 V

98250-220 220 V

98230 CHARGING SOLENOID MODULE



The 98230 Charging Solenoid Module turns the 98210-BL ACCU-CHARGE II & 98211-B ACCU-CHARGE III into Automatic Programmable Scales!

This module allows the user to control the exact amount of refrigerant transferring to and from the A/C system. The compact design is battery powered (9V), lightweight, portable and works with all types of refrigerant. The 98230 with 1/4" x 1/4" fittings includes a short hose for tank connection, USB cord and 1/4" FL - 1/2" ACME adapters.

